

Specification Sheet

Part Number: 184-11002



High Density Slotted Wall Wiring Duct, 1" X 1", Adhesive, PVC, White, 30ft/Box

Article Number	184-11002
Туре	SLHDA1X1
Color	White (WH)
Features & Benefits	•Narrow fingers reduce fanning of wires to terminal blocks, providing a neater appearance. •Each finger features a double restriction to hold wires in the bottom portion of the duct, simplifying installation. •Mounting holes are uniform in size to those in slotted and solid wall duct but are provided every two inches to accommodate compact designs and provide ease of installation. •Nonpermanent adhesive allows repositioning prior to final installation.
Quantity Per	box
Product Description	HellermannTyton High Density Slotted Wall Duct features narrow breakaway fingers, designed at a 2-to-1 ratio compared to standard slotted duct, providing

backing aids in temporary positioning.

additional access for wire leads. Narrower fingers better accommodate

compact designs and components. Pressure-sensitive, rubber-based adhesive

Short Description	High Density Slotted Wall Wiring Duct, 1" X 1", Adhesive, PVC, White, 30ft/Box
Global Part Name	SLHDA1X1-PVC-WH
Technical Description	Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.0
Width W (Metric)	25.4
Height H (Imperial)	1.06
Height H (Metric)	26.9
Mounting Hole Centers (Imperial)	2.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)

Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	UL CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013
UL Recognized (US)	Yes
Package Quantity(Imperial)	30
Package Quantity (Metric)	9.14
Customs Number	3925900000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $[\]hbox{@}$ 2018 HellermannTyton. All rights reserved.