

Part Number: 6324UL



Fire Alarm, #18-6c BC, FPLP

Product Description

Fire Alarm Cable, Plenum-FPLP, 6-18 AWG solid bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Prod	uct Over	view			
Suitab	le Applicatio	ns:	Fire Protection,	Alarm, Signal, Monitor/Detection, Audio Circuits, Control Circuits, Initiating Circuits,	Notification Circuits
Phys	ical Char	acteristics (Ov	verall)		
Condu	ctor				
AWG	Stranding	Material	No. of Conductors		
18	Solid	BC - Bare Copper	6		
Condu	ctor Count:		6		
Condu	ictor Size:		18 AWG		

Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.01 in

Color Chart

Color
Black
Red
Brown
Blue
Orange
Yellow

Outer Shield Material

Material

Unshielded

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.211 in	0.015 in	Yes

Construction and Dimensions

Cabling

Twists 3.4 twist/ft

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR 6.4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Condu	ctor
29 pF/ft	
Shielding:	Unshielded
Current	
Max. Recommended Current [A]	
3.5 Amps per conductor @ 25°C A	

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	42.2 lbs/1000ft
Max Recommended Pulling Tension:	117.6 lbs
Min Bend Radius/Minor Axis:	2.1 in

Standards

NEC Articles:	760
NEC/(UL) Specification:	FPLP
Other Specification:	California State Fire Marshall

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
UL voltage rating:	300 V RMS
Plenum/Non-Plenum	

Plenum (Y/N): Yes Part Number 5324UL

Variants

I	ltem #	Color	Footnote
	item #	Color	Footnote
I	6324UL 0021000	Red	С
1	6324UL 002U1000	Red	
1	6324UL 002A1000	Red	
Ì	Footnote:		

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief

at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.