


JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
11	2.5	.200	.200	2.51	500	C-2R
56	5.0	.115	.150	1.89	40,000	C-2R
79	6.0	.200	.630	7.92	1,000	C-2R
86	6.3	.200	.400	5.03	50,000	C-2F
18*	14.0	.040	.130	1.63	5,000	C-2F
73*	14.0	.080	.300	3.77	15,000	C-2F
37	14.0	.090	.500	6.29	2,500	C-2F
74	14.0	.100	.700	8.80	500	C-2F
85	28.0	.040	.300	3.77	25,000	C-2F
17	28.0	.065	.650	8.17	5,000	C-2F

*LAMP LEAD (Pb) FREE

CONTACT JKL FOR LEAD (Pb) FREE LOT IDENTIFICATION.



METRIC
DIMENSIONS ARE IN MILLIMETERS
TOLERANCE UNLESS OTHERWISE SPECIFIED
1 PL +/- 0.2
2 PL +/- 0.20
ANGLE +/- 0

JKL COMPONENTS CORPORATION

TITLE
T-1 3/4 STANDARD GLASS WEDGE BASE

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE
B	CHANGE #18 TO LEAD (Pb) FREE	7/12/05
A	NOTE #73 TO LEAD (Pb) FREE	2/17/05
	RELEASED & CANCEL GW-STD-T1 3/4, 75X & 84	5/11/00

DRAWN BY
L. WENGSTROM

APPVD BY DATE
J.K. 7/12/05

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

SIZE A	FSCM NO. 55335	DRAWING NO.	RELEASED DATE 5/11/00	REVISION DATE 7/12/05	REV. NO. B	SHEET 1 OF 1
SCALE NONE		TITLE GLASS WEDGE BASE T-1 3/4				