

## Special Products



### ATO® Resistor

**Part Number:** 02400100\_ series

### Specifications

**Operating Temp.:** -20°C to +85°C  
**Resistor Value:** Optional  
**Power Rating:** 1/4 W Max  
**Body Material:** Thermoplastic  
**Term. Material:** C.R.S. (Ni/Zn Plated)  
**Term. Retention:** 25 N



### ATO® Diode Part Number: 02400103\_ (Z = 1500 / LXN = 50)

1 A Diode in ATO® size housing. The cathode connector is rotated 90°

1-A-Diode in ATO®-Größe mit 90°-abgewinkeltem Kathodenanschluss.

**Operating Temp.:** -40°C to +85°C  
**Diode Rating:** 1.0 A  
**Max P.I.V.:** Optional  
**Body Material:** Thermoplastic  
**Term. Material:** C.R.S. (Ni/Zn Plated)  
**Term. Retention:** 25 N



### MINI® Resistor

**Part Number:** 02400100\_ series

**Operating Temp.:** -40°C to +85°C  
**Resistor Value:** Optional  
**Power Rating:** 1/4 W Max  
**Body Material:** Thermoplastic  
**Term. Material:** C.R.S. (Ni/Zn Plated)  
**Term. Retention:** 25 N



### MINI® Diode

**Part Number:** 02400113\_ (P= 2000 / LXN = 50)

**Operating Temp.:** -40°C to +85°C  
**Diode Rating:** 1.0 A  
**Max P.I.V.:** Optional  
**Body Material:** Thermoplastic  
**Term. Material:** C.R.S. (Ni/Zn Plated)  
**Term. Retention:** 25 N



### ATO® Shunt

**Part Number:** 02400094P (2000 pcs)

**Operating Temp.:** -40°C to +125°C  
**Maximum Continuous Load Rating:** 35A  
**Body Material:** Thermoplastic (UL 94V0 Rated)  
**Term. Material:** Brass Tin Plated



### MINI® Shunt

**Part Number:** 0297900.WXNV (3000 pcs)

MINI® size shunt for continuous load up to 20A.

Shunt in MINI®-Bauform für Dauerlasten bis 20A.

**Operating Temp.:** -40°C to +125°C  
**Maximum Continuous Load Rating:** 20A  
**Body Material:** Thermoplastic (UL 94V0 Rated)  
**Term. Material:** Zinc Silver Plated



### JCASE® Shunt

**Part Number:** 0495900.Z

**Operating Temp.:** -40°C to +125°C  
**Maximum Continuous Load Rating:** 50A  
**Body Material:** Nylon  
**Term. Material:** Copper